



Heat shrinkable tubing 2:1 - flexible and transparent

TF24

Protects wire and cable markers subject to abuse, while permitting inspectability of each item covered. Protects electronic components while permitting their identification and inspection.

Features and benefits

- Transparent, flexible polyolefin tubing
- Protects identification marking perfect
- Halogen free
- Good mechanical and chemical resistance
- VG-approval and additional industrial approvals



TF24 transparent tubing with 2:1 shrink ratio.



Cut lengths available on request. Please contact us!



One Step to the Web!

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +135 °C
Min. Shrink Temperature	+110 °C
Longitudinal change after shrinkage	+/- 5 % max.
Dielectric Strength	≥ 30 kV/mm min. according to ASTM D2171
Flammability	not flame retarded



Heat Shrinkable Tubing 2:1

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Designation as per VG-Norm	Tools	Article-No.
TF24-1.2/0.6	1.2	3/64 "	0.6	0.41	100 m	Transparent (CL)	VG 95343 T05 B 001 M	30-32	309-40123
TF24-1.6/0.8	1.6	1/16 "	0.8	0.43	100 m	Transparent (CL)	VG 95343 T05 B 002 M	30-32	309-40163
TF24-2.4/1.2	2.4	3/32 "	1.2	0.51	100 m	Transparent (CL)	VG 95343 T05 B 003 M	30-32	309-40243
TF24-3.2/1.6	3.2	1/8 "	1.6	0.51	100 m	Transparent (CL)	VG 95343 T05 B 004 M	30-32	309-40323
TF24-4.8/2.4	4.8	3/16 "	2.4	0.51	60 m	Transparent (CL)	VG 95343 T05 B 005 M	30-32	309-50483
TF24-6.4/3.2	6.4	1/4 "	3.2	0.64	60 m	Transparent (CL)	VG 95343 T05 B 006 M	30-32	309-50643
TF24-9.5/4.8	9.5	3/8 "	4.8	0.64	50 m	Transparent (CL)	VG 95343 T05 B 007 M	30-32	309-40953
TF24-12.7/6.4	12.7	1/2 "	6.4	0.64	50 m	Transparent (CL)	VG 95343 T05 B 008 M	30-32	309-41273
TF24-19.1/9.5	19.1	3/4 "	9.5	0.76	50 m	Transparent (CL)	VG 95343 T05 B 009 M	30-32	309-31903
TF24-25.4/12.7	25.4	1 "	12.7	0.89	50 m	Transparent (CL)	VG 95343 T05 B 010 M	30-32	309-32543
TF24-38.1/19.1	38.1	1-1/2 "	19.1	1.02	60 m	Transparent (CL)	VG 95343 T05 B 011 M	30-32	309-33813
TF24-50.8/25.4	50.8	2 "	25.4	1.14	60 m	Transparent (CL)	VG 95343 T05 B 012 M	30-32	309-35083
TF24-76.2/38.1	76.2	3 "	38.1	1.27	30 m	Transparent (CL)	VG 95343 T05 B 013 M	-	309-37603
TF24-101.6/50.8	101.6	4 "	50.8	1.40	15 m	Transparent (CL)	VG 95343 T05 B 014 M	-	309-31023

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.